12. COMPETITORS & EQUIPMENT

- a. Only one skimmer and one disc per plough body. Discs/skimmers/tailpieces may be of a different make.
- b. No disc stem lifting, lowering or swivelling devices are permitted
- c. Adjustable stays on plough mouldboards are permitted.
- d. Extended wheel axles are permitted.
- e. Screw adjustments on cross shafts are permitted.
- f. Modified plough shares are permitted.
- g. Adjustable Landsides are not permitted
- h. Chains are not permitted.
- i. Two-piece adjustable tailpieces are permitted and should be as designed for the plough at the time of manufacture. The dimensions of the tail piece should not exceed 14cm x 24cm. The outer end must not extend more the 26cm beyond the end of the plough mouldboard. The ratio of curvature in any plain must not exceed 1:15 The tail-piece mounting bracket must be bolted to the mould board as shown in the photograph below.



- j. Tailpieces should not be adapted to manipulate the furrows or scratches.
- k. Draw-bars with hydraulic movement not permitted.
- I. Quick entry or slotted top links are allowed
- m. Hydraulic top links and other hydraulic rams are not permitted.
- n. Four wheel drive conversions not permitted.
- o. Only approved manufacturers diesel engine conversions are permitted.
- p. Weights can be used on tractors or ploughs.
- A list of eligible tractors and ploughs is available from the European Ploughing Association on request.

13. GUIDELINES FOR ORGANISERS

- a. Tramlines plough at 90° across tramlines if possible.
- b. Avoid plots on side headlands.
- c. Recommended size of plots: length 60m; width 14m
- Recommended width of headland:
 Trailing ploughs 15 metres; Mounted ploughs 10 metres

14. FINAL DECISION

Any question arising and not provided for in the European Vintage Ploughing Rules shall be decided by the Head Stewards whose decision shall be final and binding

EUROPEAN PLOUGHING ASSOCIATION

Official Rules For The 2015 European Classic Conventional Ploughing Championships

1xth European Vintage Ploughing Championships

To be held at Veendam, the Netherlands Sunday 20th September 2015

Published February 2011

Approved Sept 2012 Revised Sept 2013

EUROPEAN PLOUGHING ASSOCIATION RULES FOR CLASSIC CONVENTIONAL PLOUGHING

1. TRACTOR

In the classic mounted plough class, all models of tractor must have been in production prior to the Q cab regulations (approximately 1976)

2. PLOUGHS

- a. Mounted Classic Ploughs to have been in productions before 31st December 1976
- b. Plough bodies to have been designed for the plough at time of manufacture.
- Skimmers and two-piece tailpieces are optional no other attachments allowed.
- d. Plough bodies can be raised or lowered but cannot be raised out of the 'ploughing' position.
- e. All plough bodies to be used when ploughing the finish.
- f. Extraneous attachments that manipulate the furrows or scratches are not allowed.

3. TIME ALLOWED

- a. 20 minutes for opening. Penalty for failure to finish opening on time 2 points per minute or part minute.
- b. 40 minutes for openings to be judged.
- c. 4 hours to complete the plot. Penalty for failure to finish the plot at finishing signal - 10 points per minute or part minute
- d. 15 minutes for any cast-off made after commencement of ploughing.

4. OPENING

- a. Double opening no land left unturned.
- b. On grassland there is no opening.

5. START

- a. The start shall consist of 15 or 16 furrows.
- b. Competitors must cast towards the next highest numbered plot.

6. FINISH

- a. The finish shall consist of the last 8 furrows.
- b. Last furrow to be cast towards competitors' own start.

7. **DEPTH OF PLOUGHING**

- a Minimum depth to be reached on completion of start and adhered to until commencing the finish.
- b Minimum depth of ploughing 17 cm ~ Maximum depth 20cm

8. GENERAL

- a. The first and second runs next to the neighbours' plot will be allowed as straightening furrows and will not be judged.
- b. Rolling of furrows or scratches is **not** allowed (including neighbours' furrows).
- c. Twin tractor wheels not allowed.
- d. Three sighting poles only (one may be placed on the headland) assistance to set and remove is allowed. No other assistance allowed including no assistance by signal, radio contact, mobile phone or any other method.
- e. Handling, shaping or treading of scratches or furrows is **not** allowed.
- f. Only one tractor wheel mark allowed at the finish.
- g. Only the competitor allowed to clean the plot of straw, stones, etc. Clearing of stubble not allowed and will be penalised.
- h. Only Three idle rounds are permitted between making the opening Split and the finishing furrow.
- i. Competitors must produce evidence of age of tractor if required
- The use of Global Positioning Technology, laser beams or any other electronic or computerised measuring devices are not allowed

k. Any abuse or by a competitor with an official or fellow competitor is not acceptable. Penalty - 20 points

9. SAFETY

- a. Passengers not allowed on tractors or ploughs at any time.
- b. The Safety Policy to be adhered to at all times.

10. FIXED PENALTY DEDUCTIONS

Rolling of furrows or scratches (including neighbours furrows) .	20 points penalty
More than one wheel mark at the finish	20 points penalty
Casting the finish the wrong way	20 points penalty
Failure to plough the specified depth (per cm or part thereof below specified depth)	20 points penalty
Failure to finish opening on timeor part min over time	2 points per minute
Failure to finish plot by finishing signal or part min over time	10 points per minute
Failure to adhere to the Safety Policy	Disqualification

Any other infringements will be decided by the Head Stewards.

11. JUDGES METHOD OF SCORING

JUDGES WETHOD OF SCORING		
OPENING SPLIT, Completeness of cutting through the sod throughout the whole length & width of opening the split. Uniformity & Neatness	10 Pc	oints
CROWN (START) (15 or 16 furrows, Uniform & level)	40 Pc	oints
GENERAL (Middle) WORK No stubble, grass or weeds. Skimmers must be used; furrow slices closed, firm & no holes. No tractor wheel marks. Uniformity & conformity of furrow slices, Soil made available for seed bed	80 P	oints
INS AND OUTS (Neat, accurate and regular, No tractor wheel marks	10 P	oints
FINISH (Last 8 Furrows) Neatness, No weed or trash, Finishing furrow slices closed & uniform. Shallow & only. one tractor wheel mark	40 P	oints
GENERAL APPEARANCE		
(All Aspects of Workmanship. Excellence over the entire plot.)	20 P	oints
STRAIGHTNESS: Measured four times i.e. Opening Split, Crown, General Work & Finish	20 P ¢	oints
Note: All points awarded for straightness will be added together and divided	by 2	

Ties: - In the event of two or more competitors scoring equal points then the Scrutineers shall use the "Count Back" system to resolve the tie. Referring to aspects in the following sequence. :-

a) General Work, b) Crown, c) Finish d) Straightness e) General Appearance f) Opening Split g) Ins & Outs